

ETERNABOND[®]

APPLICATION INSTRUCTIONS



1

Locate the area of your RV needing repair.



2

Clean the surface and allow it to dry completely.

Recommended cleaners: EternaClean™, lacquer thinner, acetone, commercial roof cleaner, etc. Do not use detergent type cleaners.

(If old Hypalon®, PVC or TPO, score the repair area with sand paper, then wipe off the dust.)



3

Start the removal of the release liner. (See Other Side)



4

Apply the tape to the surface.



5

Apply pressure to activate bonding process. Use a steel roofer's roller for best results. The firmer the pressure of rubbing applied, the faster and better the bond.

RELEASE LINER REMOVAL INSTRUCTIONS





LINER REMOVAL INSTRUCTIONS



1

Grab outer edges with thumb and forefingers.



2

Push fingers together, bunching the tape in the middle.



3

In a fast motion, snap the tape forward and backward.



4

Repeat step three seven to ten times.



5

Push fingers together again, allowing the liner to “pop” from the tape.



6

Peel the liner from the tape and apply to the prepared surface.

For more information about our company, visit eternabond.com

IMPORTANT: Information, specifications, procedures and recommendations provided (“information”) are based on our experience and we believe this to be accurate. No representation, guarantee or warranty is made as to the accuracy or completeness of the information or that use of the product will avoid losses or damages or give desired results. It is user’s sole responsibility to test and determine the suitability of any product for the intended use. Tests should be repeated if materials or conditions change in any way. The user is advised to review the specific context of the intended use to determine whether the user’s intended use violates any law or infringes upon any patent(s). No employee, distributor or agent has any right to change these facts and offer a guarantee of performance.

Unless otherwise noted, trademarks are property of H.B. Fuller Company or one of its affiliated entities. Hypalon is a registered trademark of DuPont Performance Elastomers L.L.C.

© H.B. Fuller Company, 2025

APPLICATION INSTRUCTIONS

